

# SRM

The SRM is an economical short-range rotor that offers a convenient and efficient alternative to spray heads.

Radius: **4.0 to 9.4 m**  
Flow: **0.08 to 0.82 m<sup>3</sup>/hr; 1.4 to 13.7 l/min**

ROTORS

## KEY BENEFITS


- Adjustable arc from 40° to 360° to keep water in the appropriate areas
- Standard factory-installed 2.0 nozzle speeds installation
- QuickCheck™ arc mechanism for fast arc adjustment

## OPERATING SPECIFICATIONS

- Nozzle choices: 6
- Radius: 4.0 to 9.4 m
- Flow: 0.08 to 0.82 m<sup>3</sup>/hr; 1.4 to 13.7 l/min
- Recommended pressure range: 1.7 to 3.8 bar; 170 to 380 kPa
- Operating pressure range: 1.4 to 7.0 bar; 140 to 700 kPa
- Precipitation rate: 11 mm/hr approximately
- Nozzle trajectory: 14° approximately
- Warranty period: 2 years

## USER-INSTALLED OPTIONS

- Drain check valve (up to 2.1 m of elevation) (P/N 462078SP)

SRM		SRM NOZZLES
Model	Description	
SRM-04	10 cm pop-up, adjustable arc, 6 standard nozzles	



### SRM-04

Overall height: 18 cm  
Pop-up height: 10 cm  
Exposed diameter: 3 cm  
Inlet size: ½"

## SRM GREEN NOZZLE PERFORMANCE DATA

Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m <sup>3</sup> /hr	l/min	■	▲
<b>.50</b> ● Dk. Green	1.7	170	4.0	0.08	1.4	11	12
	2.0	200	4.3	0.09	1.6	10	12
	2.5	250	4.3	0.11	1.8	12	14
	3.0	300	4.6	0.12	2.0	12	13
	3.5	350	4.6	0.13	2.2	13	15
	3.8	380	4.9	0.14	2.3	12	14
<b>.75</b> ● Dk. Green	1.7	170	4.9	0.13	2.2	11	13
	2.0	200	5.2	0.14	2.4	11	12
	2.5	250	5.2	0.16	2.7	12	14
	3.0	300	5.5	0.18	3.0	12	14
	3.5	350	5.5	0.19	3.2	13	15
	3.8	380	5.8	0.20	3.4	12	14
<b>1.0</b> ● Dk. Green	1.7	170	5.8	0.18	2.9	11	12
	2.0	200	6.1	0.19	3.2	10	12
	2.5	250	6.1	0.21	3.5	11	13
	3.0	300	6.4	0.24	3.9	12	13
	3.5	350	6.4	0.25	4.2	12	14
	3.8	380	6.7	0.26	4.4	12	14
<b>1.5</b> ● Dk. Green	1.7	170	6.7	0.27	4.5	12	14
	2.0	200	7.0	0.29	4.8	12	14
	2.5	250	7.0	0.32	5.4	13	15
	3.0	300	7.3	0.36	6.0	13	16
	3.5	350	7.3	0.39	6.5	15	17
	3.8	380	7.6	0.40	6.7	14	16
<b>2.0</b> ● Dk. Green	1.7	170	7.3	0.35	5.8	13	15
	2.0	200	7.9	0.38	6.3	12	14
	2.5	250	7.9	0.43	7.1	14	16
	3.0	300	8.2	0.48	8.0	14	16
	3.5	350	8.2	0.53	8.8	16	18
	3.8	380	8.5	0.55	9.2	15	17
<b>3.0</b> ● Dk. Green	1.7	170	8.2	0.51	8.5	15	17
	2.0	200	8.5	0.56	9.3	15	18
	2.5	250	8.5	0.64	10.6	17	20
	3.0	300	9.1	0.72	12.0	17	20
	3.5	350	9.1	0.78	13.1	19	22
	3.8	380	9.4	0.82	13.7	18	21

### Note:

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2.

## SRM



Compatible with:



**SJ Swing Joints**  
Page 68



**Hunter FlexSG**  
Page 68