

RESIDENTIAL & COMMERCIAL IRRIGATION Built on Innovation®



- 01 Flexible design: Modular options offer conventional wiring up to 23 stations, or choose fixed 6- or 12-station models
- **O2 Two-wire compatible:** Enable hybrid two-wire control up to 32 stations with EZ-1 decoders
- 03 Smart water savings: Solar Sync[™] compatibility provides automatic watering adjustments based on local weather conditions

PRO-C[™] RESIDENTIAL & LIGHT COMMERCIAL CONTROLLER

Simple programming, flexible station expansion, and optional two-wire capabilities make the user-friendly Pro-C controller the professional's first choice for residential and light commercial systems. When expansion isn't necessary, the fixed 6- and 12-station models offer affordability in a high-end residential controller.

Pro-C users can now add more stations than ever before, in the same compact package they've come to know and trust. Compatibility with simple and affordable two-wire control makes the Pro-C the perfect solution for light commercial projects such as business parks, city parks, schools, and multi-family housing complexes.

The Pro-C and all AC-powered Hunter controllers are Smart WaterMark approved when paired with a Solar Sync weather sensor. Solar Sync calculates evapotranspiration (ET) and adjusts Hunter controllers daily based on local weather conditions, resulting in maximum water savings.





Learn more. Visit hunterindustries.com for more detailed information.

PRO-C

Simple programming and flexible station expansion make Pro-C the professional's choice for residential and light commercial systems.

KEY BENEFITS

- Number of stations:
 - Modular Pro-C
 - Conventional wiring from 4 to 23 stations
 - Hybrid EZ Decoder option up to 32 total stations
 - (28 stations max. if two-wire only)
- Fixed PCC with 6- and 12-station options3 independent irrigation programs (4 start times each) allow for
- customised scheduling
- 1 sensor input available for use with Solar Sync™ or any Clik sensors
- 1 P/MV output for pump start relay and master valve activation
- Dedicated Solar Sync dial position provides logic for smart water savings
 Easy Retrieve™ memory allows for manual backup and retrieval of
- Easy Refrese milenoity allows for manual backup and refrese of preferred settings and programming
- $\mathsf{QuickCheck^{m}}$ provides simple diagnostics of faulty field wiring

OPERATING SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Approvals: UL, cUL, FCC, CE, RCM
- Warranty period: 2 years

PC-SERIES STATION EXPANSION	
Modules	Description
PCM-300	3-station plug-in module
PCM-900	9-station plug-in module (maximum, one per controller)
PCM-1600-KIT	Upgrade kit for 16-station plug-in module
PC-DM-KIT	Upgrade kit for EZ decoder output module

PRO-C - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4 Model 2 Transformer 3 Indoor/Outdoor 4 Options PC-4 = 4-station base **00** = 120 VAC (blank) = Outdoor model (blank) = No option module controller (internal transformer) i = Indoor model E = 230 VAC with PCC-6 = 6-station 01 = 230 VAC (plug-in transformer) European connections PCC-12 = 12-station A = 230 VAC with Australian connections



PC-400 = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet **PCC-601i-E** = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet

PCC-1200 = Fixed 12-station outdoor controller, internal 120 VAC transformer, and plastic cabinet

Website hunterindustries.com | Customer Support 1-760-752-6037 | Technical Service +1760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.







(outdoor models have

internal transformer with cord)



Plastic Indoor Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm



Plastic Outdoor Height: 22.9 cm Width: 25.4 cm Depth: 11.4 cm

Compatible with:





ROAM XL

Remote

Solar Sync F Sensor e EZ Decoder System



Smart WaterMark Recognised as a responsible water-saving tool when used with a Solar Sync sensor