

# PRS40

To optimise MP Rotator performance, the PRS40 is pressure-regulated to 2.8 bar; 280 kPa.

## KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Pressure-regulated to 2.8 bar; 280 kPa for the MP Rotator
- Grey cap for easy field identification
- Co-moulded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- FloGuard technology option eliminates water waste in the event of a missing nozzle

## ADDITIONAL FEATURES

- Directional flush plug design for cleaner installation
- Interchangeable components for easier servicing, retrofits, and upgrades
- Heavy-duty spring for consistent riser retraction
- Check valve comes standard (4.3 m of elevation)

## OPERATING SPECIFICATIONS

- Operational pressure range: 1.0 to 7.0 bar; 100 to 700 kPa
- Warranty period: 5 years

## FACTORY-INSTALLED OPTIONS

- Reclaimed water identification
- FloGuard technology available for pop-up models

## USER-INSTALLED OPTIONS

- Reclaimed water ID cap (P/N 458562SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP-SP)
- Shutoff cap (P/N 213600SP)
- Shutoff nozzle (P/N 916400SP)



### PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps.



**PROS-00-PRS40**  
Retracted height: 11 cm  
Inlet size: ½"



**PROS-04-PRS40-CV**  
Retracted height: 15.5 cm  
Pop-up height: 10 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"



**FloGuard Technology**



**PROS-06-PRS40-CV**  
Retracted height: 22.5 cm  
Pop-up height: 15 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"



**PROS-12-PRS40-CV**  
Retracted height: 41 cm  
Pop-up height: 30 cm  
Exposed diameter: 5.7 cm  
Inlet size: ½"

SPRAYS

## PRS40 – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Specialty Options
<b>PROS-00-PRS40</b> = 2.8 bar regulated shrub adapter	<b>(blank)</b> = No option
<b>PROS-04-PRS40-CV</b> = 2.8 bar regulated 10 cm pop-up with drain check valve	<b>R</b> = Factory-installed reclaimed body cap
<b>PROS-06-PRS40-CV</b> = 2.8 bar regulated 15 cm pop-up with drain check valve	<b>F</b> = FloGuard technology
<b>PROS-12-PRS40-CV</b> = 2.8 bar regulated 30 cm pop-up with drain check valve	<b>F-R</b> = FloGuard technology with reclaimed body cap

### Examples:

**PROS-04-PRS40-CV** = 10 cm pop-up regulated at 2.8 bar, drain check valve

**PROS-06-PRS40-CV-F** = 15 cm pop-up regulated at 2.8 bar, drain check valve, with FloGuard technology

**PROS-12-PRS40-CV-R** = 30 cm pop-up regulated at 2.8 bar, drain check valve, reclaimed body cap

Compatible with:



**MP Rotator**  
Page 52 and Page 56