

MULTI-PORT EMITTER

Pressure Compensating Flow: **2.0, 4.0, 8.0, 15.0l/hr**

FEATURES

- Unused ports may be closed using vinyl emitter caps
- Pressure-compensating
- Perfect for mixed plantings or series of shrubs
- Flows are colour-coded to match other Hunter emitters
- ½" FPT
- Commercial-grade for all PVC systems
- Manifold available
- Warranty period: 2 years

OPERATING SPECIFICATIONS

- Recommended Pressure: 0.4 to 4.5 bar; 4 to 450 kPa
- Minimum Filtration: 150 mesh; 100 microns

MULTI-PORT EMITTER MODEL CHART

	Model	Flow (l/hr)
● Blue	MPE-05	2.0
● Black	MPE-10	4.0
● Red	MPE-20	8.0
● Tan	MPE-40	15.0
● Grey	MPM-050	N/A



Multi-Port Emitter



MULTI-PORT MANIFOLD

(MPM-050)

Unrestricted flow through outlets as indicated by grey colour. Use with 6 mm distribution tubing and a barbed emitter at the end (Available in ½" FPT). Allows water to be directed to as many as six different locations.

EMITTER CAPS

(MPE-CAPS)

Plugs unused 6 mm barbed emitter outlets. Use with Hunter Multi-Port Emitters.



RIGID RISER

Surface Irrigation: **Height Adjustment**

FEATURES

- For rugged system designs
- Accepts 10-32 threaded components
- Perfect for annual flower beds and planters
- Inlet configurations: ½" FPT, 6 mm barb, or blank
- HDPE construction
- Warranty period: 1 year

RIGID RISER MODEL CHART

Model	Description
RR12	30 cm rigid riser
RR12-T	30 cm rigid riser with ½" threaded base
RR12-B	30 cm rigid riser with 6 mm barb base
RR18	45 cm rigid riser
RR18-T	45 cm rigid riser with ½" threaded base
RR18-B	45 cm rigid riser with 6 mm barb base



30 cm Rigid Riser



45 cm Rigid Riser